



Submittal Data

MODEL
REG-123M

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 1Ph,230/208V-,60Hz

Cooling

Capacity	Btu/h	12,000/11,600
Input	W	1100/1064
Rated current	A	5.0/5.2
Max. Current	A	7.4
CEER	Btu/w	10.9
EER		10.9

Heating

Capacity	Btu/h	11,000/8,500
RATED Input(Heater)	W	3450/2821
Rated current	A	16/14.5

Compressor Electrical

Model	ASM106N1VEZ	
Type	Rotary	
Brand	GMCC	
Capacity	Btu/h	12573
Input	W	855
Rated current(RLA)	A	4.05
Refrigerant type	oz	R410A/22.22

Air flow & Noise level

Indoor air flow	CFM	279/255/223
Indoor noise level	dB(A)	60.9/58.3/54.7
Outdoor air flow	CFM	696/633/553
Outdoor noise level	dB(A)	67.2/64.4/60.8
Window Opening	Min/Max Width	26.8/36
	Min Height	16.5

Accessories

AS080	Window AC Support Bracket
NTN-2	Window AC Support Bracket



Fan Motor

Model	YKTS-95-4-1	
Input	W	142/127/112
Speed	RPM	1500/1380/1240

Dimensional Data

Dimension(W*D*H)	inch	22.6x23x16.1
Packing (W*D*H)	inch	25x28.3x17
Net/Gross weight	lbs.	70.6/82

SYSTEM DATA

Design pressure	PSIG	300/520
Thermostat type	Touchpad/Remote	
Application area (Cooling EPA)	450-550	

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-20P

